



## TS-1273AU-RP-8G

CPU	AMD Ryzen™ Embedded V1500B 4-core/8-thread 2.2 GHz processor
CPU Architecture	64-bit x86
Floating Point Unit	Yes
Encryption Engine	Yes (AES-NI)
Hardware-accelerated Transcoding	Optional via a PCIe graphics card
System Memory	8 GB UDIMM DDR4 (1 x 8 GB)
Maximum Memory	64 GB (2 x 32 GB)
Memory Slot	2 x UDIMM DDR4 Support ECC memory  For dual-DIMM configuration, you must use a pair of identical DDR4 modules.
Flash Memory	5GB (Dual boot OS protection)
Drive Bay	12 x 3.5-inch SATA 6Gb/s, 3Gb/s  The system is shipped without HDD. For the HDD compatibility list, please visit <a href="https://www.qnap.com/compatibility/">https://www.qnap.com/compatibility/</a>
Drive Compatibility	3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Hot-swappable	Yes (Not supported M.2 SSD)
M.2 Slot	Optional via a QNAP QM2 PCIe card
SSD Cache Acceleration Support	Yes
GPU pass-through	Yes
2.5 Gigabit Ethernet Port (2.5G/1G/100M)	2 (2.5G/1G/100M)
5 Gigabit Ethernet Port (5G/2.5G/1G/100M)	Optional via a network adapter

10 Gigabit Ethernet Port	Optional via a network adapter
Wake on LAN (WOL)	Yes  Only the 2.5GbE port
Jumbo Frame	Yes
PCIe Slot	2 x PCIe Gen3 x4  With a riser card (two PCIe slots): slot 1:160 x 68.9x 18.76 mm / 6.3 x 2.71 x 0.74 inches. slot 2:160 x 68.9x 39.08 mm / 6.3 x 2.71 x 1.54 inches. Wider cards can be installed if the next PCIe slot will not be used. Without a riser card (one PCIe slot): Slot 1:160 x 68.9x 39.08 mm / 6.3 x 2.71 x 1.54 inches.
USB 3.2 Gen 1 port	1 x Type-A
USB 3.2 Gen 2 (10Gbps) Port	2 x Type-C 1 x Type-A
HDMI™ Output	Optional via a PCIe graphics card
Form Factor	2U Rackmount
LED Indicators	HDD 1-12, Status, LAN, USB, Power
Buttons	Power, Reset
Dimensions (HxWxD)	88.6 × 432 × 370.7 mm  Excludes ear hook and the protruding part of the Power Supply Unit.
Weight (Net)	11.13 kg
Weight (Gross)	14.62 kg
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	300W (x2) PSU, 100 - 240V
Power Consumption: Disk Standby Mode	43.67
Power Consumption: Operating Mode, Typical	78.92 W  Tested fully populated with WD10EFRX hard drives.
Fan	2 x 80mm, 12VDC
System Warning	Buzzer
Standard Warranty	3

Max. Number of Concurrent Connections (CIFS) - with Max. Memory	2000
---	------

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications and refer to the hardware user manual to install compatible QNAP memory modules.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.